

- FAX.IR REST API v2.1.0
- Authentication
  - OAuth2 authentication
- Accounts
- Numbers
  - listNumbers
  - getNumber
  - updateNumber
  - revokeNumber
- Archives
- Files
  - uploadFile
  - getFile
- Outbox
  - listOutboxFaxes
  - sendFax
  - getOutboxFax
  - deleteOutboxFax
  - updateOutboxFax
- Schemas
  - Outbox
  - Fax
  - Number
  - Account
  - File
  - MemberDetail
  - Error

FAX.IR REST API v2.1.0

> Scroll down for code samples, example requests and responses. Select a language for code samples from the tabs above or the mobile navigation menu.

This is the fax.ir API v2 developed for third party developers and organizations. In order to have a better coding experience with this API, let's quickly go through some points:

- This API assumes **/accounts** as an entry point with the base url of **https://api.fax.ir/v2**.

- This API treats all date and times sent to it in requests as **UTC**. Also, all dates and times returned in responses are in **UTC**

- Once you have an access_token, you can easily send a request to the resource server with the base url of **https://api.fax.ir/v2** to access

your permitted resources. As an example to get the user's profile info you would send a request to **https://api.fax.ir/v2/accounts/self** when **Authorization** header is set to "Bearer YOUR_ACCESS_TOKEN" and custom header of **x-fax-clientid** is set to YOUR_CLIENT_ID

Base URLs:

- https://api.fax.ir/v2

Github: https://github.com/faxir

Authentication

OAuth2 authentication

DESCRIPTION

Authorization Code Grant

The first step is to obtain an authorization code by redirecting the user to the `https://accounts.fax.ir/login` website and asking permission from the user. The redirection request would be in the format of `https://accounts.fax.ir/login?response_type=code&client_id=YOUR_CLIENT_ID&redirect_uri=ONE_OF_YOUR_REGISTERED_URIS&scope=SPACE_SEPARATED_LIST_OF_REQUESTED_SCOPES`.
Let's assume we have `http://localhost` as the registered URI and we want to request permission for scope `all`. So this would be the redirection uri: `https://accounts.fax.ir/login?response_type=code&client_id=YOUR_CLIENT_ID&redirect_uri=http://localhost&scope=all`
In the redirected page, the user will be asked for his username and password and review your requested permissions. If the user accepts to give the permissions to the client, he would be redirected to the given redirect uri, appended with the authorization code as `http://localhost?code=XXXXXX`
The next step is to obtain an access token. The client must send a HTTP POST request with the `Content-type` of `application/x-www-form-urlencoded` containing client credentials, redirect_uri provided in previous request, and finally code given in last step.: `https://accounts.fax.ir/token?grant_type=authorization_code&client_id=YOUR_CLIENT_ID&code=AUTHORIZATION_CODE_FROM_PREVIOUS_STEP&redirect_uri=http://localhost`
NOTE: In this request you have to set the HTTP Authorization header as `Basic BASE64_ENCODEDED_VALUE_OF(CLIENT_ID:CLIENT_SECRET)`. In case of successful request you would be granted an access token.

Refeshing An Access Token

In case your access token gets expired, to renew your token pass the refresh token that you have received when obtaining an access token to https://accounts.fax.ir/token?grant_type=refresh_token&refresh_token=REFRESH_TOKEN while have Authorization header set to Basic BASE64_ENCODEDED_VALUE_OF(CLIENT_ID:CLIENT_SECRET)

NOTE:the refresh token remains valid until either user revokes the permissions given to the client or being used to acquire a new access token. In latter case, a new refresh token would be provided alongside the given access token.

FLOWS

FLOW: AUTHORIZATIONCODE

- Authorization URL = https://accounts.fax.ir/login?response_type=code&client_id=YOUR_CLIENT_ID&redirect_uri=http://localhost&scope=all
- Token URL = https://accounts.fax.ir/token

Scope	Scope Description
all	for now when a user grant permission, all grants will be permitted

Accounts

getAccounts

Code samples

```ruby
require 'rest-client'
require 'json'

headers = {
  'Accept' => 'application/json'
}

result = RestClient.get 'https://api.fax.ir/v2/accounts',
  params: {
  }, headers: headers

p JSON.parse(result)
```

`GET /accounts`

Get account information of all members of your corporate account

Only admin account can send request to this endpoint which returns accounts of all members

RESPONSES

Status	Meaning	Description
200	OK	No description
400	Bad Request	No description
500	Internal Server Error	No description

---

getUser

Code samples

```ruby
require 'rest-client'
require 'json'

headers = {
  'Accept' => 'application/json'
}

result = RestClient.get 'https://api.fax.ir/v2/accounts/{user_id}',
  params: {
  }, headers: headers

p JSON.parse(result)
```

`GET /accounts/{user_id}`

Get account information for admin or member

Get account information. For members user_id can only be self. form admin it can be user_id of any
In case you want to get your own account information please use `self` as an alias for your user_id.

PARAMETERS

Parameter	In	Type	Required	Description
user_id	path	string	true	No description

RESPONSES

Status	Meaning	Description
200	OK	No description
400	Bad Request	No description
500	Internal Server Error	No description

---

updateUser

Code samples

```ruby
require 'rest-client'
require 'json'

headers = {
  'Content-Type' => 'application/json',
  'Accept' => 'application/json'
}

result = RestClient.put 'https://api.fax.ir/v2/accounts/self',
  params: {
  }, headers: headers

p JSON.parse(result)
```

`PUT /accounts/self`

Modify account information

You can only modify your account

Body parameter

```
{
  "account_data": {
    "company_name": "Company name",
    "default_file_type": "pdf",
    "save_history": true
  },
  "account_type": "corporate_admin",
  "creation_date": "2017-05-06 05:22:21",
  "email": "sample@fax.ir",
  "last_password_modification_date": "2017-05-06 05:22:21",
  "lastname": "Smith",
  "member_of": {},
  "notifications": {
    "black_list": {
      "uids": []
    },
    "settings": {
      "email": {
        "addresses": [
          "sample@fax.ir"
        ],
        "low_credit": true,
        "new_feature": true,
        "receive_fax": true,
        "send_fax": true,
        "voicemail": true
      },
      "language": "fa",
      "push_notifications": {
        "low_credit": true,
```

```
        "new_feature": true,
        "receive_fax": true,
        "send_fax": true,
        "voicemail": true
      },
      "sms": {
        "low_credit": true,
        "new_feature": true,
        "numbers": [
          "+989350000000"
        ],
        "receive_fax": true,
        "send_fax": true,
        "voicemail": true
      }
    }
  },
  "phone": "+989350000000",
  "profile_image": "",
  "settings": {
    "caller_id_name": "FAX.IR",
    "send_fax": {
      "options": {},
      "retry": {
        "count": 0,
        "delay": 0
      },
      "should_enhance": true
    }
  },
  "status": "active",
  "uid": "7724157c0974440293e45877c57f0703"
}
```


PARAMETERS

Parameter	In	Type	Required	Description
user_id	path	string	true	No description
body	body	Account	false	Request object for making changes in account

RESPONSES

Status	Meaning	Description
204	No Content	Modify account information
400	Bad Request	No description
500	Internal Server Error	No description

getMemberDetails

Code samples

```ruby
require 'rest-client'
require 'json'

headers = {
  'Accept' => 'application/json'
}

result = RestClient.get 'https://api.fax.ir/v2/accounts/self/member-details/{member_id}',
  params: {
```

```
  }, headers: headers

p JSON.parse(result)
```

`GET /accounts/self/member-details/{member_id}`

Get member details

Get your member details (quota and role)

PARAMETERS

Parameter	In	Type	Required	Description
member_id	path	string	true	No description

RESPONSES

Status	Meaning	Description
200	OK	No description
400	Bad Request	No description
500	Internal Server Error	No description

---

updateMemberDetails

Code samples

```
require 'rest-client'
require 'json'

headers = {
  'Content-Type' => 'application/json',
  'Accept' => 'application/json'
}

result = RestClient.put 'https://api.fax.ir/v2/accounts/self/member-details/{member_id}',
  params: {
  }, headers: headers

p JSON.parse(result)
```

`PUT /accounts/self/member-details/{member_id}`

Modify member details

One of the paramters below is needed to modify member information

Body parameter

```
{
  "quota": 400,
  "role": "Sales Manager"
}
```

PARAMETERS

Parameter	In	Type	Required	Description

Parameter	In	Type	Required	Description
member_id	path	string	true	No description
body	body	MemberDetail	false	Request object for making changes in member details

RESPONSES

Status	Meaning	Description
204	No Content	Modify account information
400	Bad Request	No description
500	Internal Server Error	No description

Numbers

listNumbers

Code samples

```
require 'rest-client'
require 'json'

headers = {
  'Accept' => 'application/json'
}

result = RestClient.get 'https://api.fax.ir/v2/accounts/self/numbers',
  params: {
  }, headers: headers

p JSON.parse(result)
```

`GET /accounts/self/numbers`

Get your numbers

List all your purchased numbers

RESPONSES

Status	Meaning	Description
200	OK	No description
400	Bad Request	No description
500	Internal Server Error	No description

getNumber

Code samples

```ruby
require 'rest-client'
require 'json'

headers = {
  'Accept' => 'application/json'
}

result = RestClient.get 'https://api.fax.ir/v2/accounts/self/numbers/{number}',
  params: {
  }, headers: headers

p JSON.parse(result)
```

`GET /accounts/self/numbers/{number}`

Get number information

Get info of a single number

PARAMETERS

Parameter	In	Type	Required	Description
number	path	string	true	No description

RESPONSES

Status	Meaning	Description
200	OK	No description
400	Bad Request	No description
500	Internal Server Error	No description

---

updateNumber

Code samples

```ruby
require 'rest-client'
require 'json'

headers = {
  'Content-Type' => 'application/json',
  'Accept' => 'application/json'
}

result = RestClient.put 'https://api.fax.ir/v2/accounts/self/numbers/{number}',
  params: {
  }, headers: headers

p JSON.parse(result)
```

`PUT /accounts/self/numbers/{number}`

Assign number

With this API call you will be able to assign a specific number to a specific account (one of your members).

Body parameter

```
{
  "assigned_to": "string"
}
```

PARAMETERS

Parameter	In	Type	Required	Description
number	path	string	true	No description
body	body	NumberModification	false	Request object for making changes in number object
» assigned_to	body	string	false	No description

RESPONSES

Status	Meaning	Description
204	No Content	Assign an already purchased number to your members
400	Bad Request	No description
500	Internal Server Error	No description

revokeNumber

Code samples

```
require 'rest-client'
require 'json'

headers = {
  'Accept' => 'application/json'
}

result = RestClient.delete 'https://api.fax.ir/v2/accounts/self/numbers/{number}',
  params: {
  }, headers: headers

p JSON.parse(result)
```

`DELETE /accounts/self/numbers/{number}`

Revoke number

Revoke a specific number from your corporate member

PARAMETERS

Parameter	In	Type	Required	Description
number	path	string	true	No description

RESPONSES

Status	Meaning	Description
204	No Content	Revoke number from member that owns fax number
400	Bad Request	No description

Status	Meaning	Description
500	Internal Server Error	No description

Archives

listFaxes

Code samples

```ruby
require 'rest-client'
require 'json'

headers = {
  'Accept' => 'application/json'
}

result = RestClient.get 'https://api.fax.ir/v2/accounts/{user_id}/archives',
  params: {
  }, headers: headers

p JSON.parse(result)
```

`GET /accounts/{user_id}/archives`

Get fax records

With this API call you will be able to retrieve a collection of faxes (either sent or received or spam based on the category selected). If you want to filter your archive please provide the `category` parameter

PARAMETERS

Parameter	In	Type	Required	Description
user_id	path	string	true	'self' or user id of a corporate member
category	query	string	false	Category parameter can be one of these values: **inbox**, **sent**, **spam**
after	query	string	false	Start date to get records from that date
before	query	string	false	End date to get records before that date
limit	query	integer	false	Limit of fax records you want to get per request

RESPONSES

Status	Meaning	Description
200	OK	No description
400	Bad Request	No description
500	Internal Server Error	No description

getFax

Code samples

```
require 'rest-client'
require 'json'

headers = {
  'Accept' => 'application/json'
}

result = RestClient.get 'https://api.fax.ir/v2/accounts/self/archives/{fax_id}',
  params: {
  }, headers: headers

p JSON.parse(result)
```

`GET /accounts/self/archives/{fax_id}`

Get a fax record

Get a specific fax record details like duration, pages etc.

PARAMETERS

Parameter	In	Type	Required	Description
fax_id	path	string	true	No description

RESPONSES

Status	Meaning	Description
200	OK	No description
400	Bad Request	No description
500	Internal Server Error	No description

---

updateFax

Code samples

```
require 'rest-client'
require 'json'

headers = {
  'Content-Type' => 'application/json',
  'Accept' => 'application/json'
}

result = RestClient.put 'https://api.fax.ir/v2/accounts/self/archives/{fax_id}',
  params: {
  }, headers: headers

p JSON.parse(result)
```

`PUT /accounts/self/archives/{fax_id}`

Modify fax record

You can modify a fax record's comment or mark it as read

Body parameter

```
{
  "is_read": true,
  "comment": "string"
}
```

PARAMETERS

Parameter	In	Type	Required	Description
fax_id	path	string	true	No description
body	body	FaxModification	false	Request object for making changes in a fax object
» is_read	body	boolean	false	No description
» comment	body	string	false	No description

RESPONSES

Status	Meaning	Description
204	No Content	fax updated successfully
400	Bad Request	No description
500	Internal Server Error	No description

---

deleteFax

Code samples

```
require 'rest-client'
require 'json'

headers = {
  'Accept' => 'application/json'
}

result = RestClient.delete 'https://api.fax.ir/v2/accounts/self/archives/{fax_id}',
  params: {
  }, headers: headers

p JSON.parse(result)
```

`DELETE /accounts/self/archives/{fax_id}`

Delete a fax

Delete a specific fax record by providing its id

PARAMETERS

Parameter	In	Type	Required	Description
fax_id	path	string	true	No description

Example responses

```
{}
```

RESPONSES

Status	Meaning	Description
204	No Content	204 will be return on successful CDR modification
400	Bad Request	No description
500	Internal Server Error	No description

STATUS CODE 204

{}

Files

uploadFile

Code samples

```ruby
require 'rest-client'
require 'json'

headers = {
  'Content-Type' => 'multipart/form-data',
  'Accept' => 'application/json'
}

result = RestClient.post 'https://api.fax.ir/v2/accounts/self/files',
  params: {
  }, headers: headers

p JSON.parse(result)
```

`POST /accounts/self/files`

upload a file

Before sending a fax you need to upload your files using this API. In order to upload your fax file, you have to send a `multipart/form-data` request with your file. If the upload was successful you would receive a `file_path` which you can use to send your fax.

Body parameter

```yaml
fax_file: string
```

PARAMETERS

Parameter	In	Type	Required	Description
format	query	string	false	can be 'pdf' or 'tiff'
body	body	File	false	A file to be uploaded
» fax_file	body	string(binary)	false	No description

RESPONSES

Status	Meaning	Description

Status	Meaning	Description
201	Created	No description
400	Bad Request	No description
500	Internal Server Error	No description

---

getFile

Code samples

```ruby
require 'rest-client'
require 'json'

headers = {
  'Accept' => 'application/pdf'
}

result = RestClient.get 'https://api.fax.ir/v2/accounts/self/files/{fax_id}',
  params: {
  }, headers: headers

p JSON.parse(result)
```

`GET /accounts/self/files/{fax_id}`

get a file

Get your fax archive file using it's id.

PARAMETERS

Parameter	In	Type	Required	Description
fax_id	path	string	true	No description
format	query	string	false	can be 'pdf' or 'tiff'

Example responses

RESPONSES

Status	Meaning	Description
200	OK	CDR file content in corresponding mimetype e.g. application/pdf
400	Bad Request	No description
500	Internal Server Error	No description

Outbox

---

listOutboxFaxes

Code samples

```ruby
require 'rest-client'
require 'json'

headers = {
  'Accept' => 'application/json'
}

result = RestClient.get 'https://api.fax.ir/v2/accounts/self/outbox',
  params: {
  }, headers: headers

p JSON.parse(result)
```

`GET /accounts/self/outbox`

Get outbox records

Get outbox fax records information

RESPONSES

Status	Meaning	Description
200	OK	No description
400	Bad Request	No description
500	Internal Server Error	No description

---

sendFax

Code samples

```ruby
require 'rest-client'
require 'json'

headers = {
  'Content-Type' => 'application/json',
  'Accept' => 'application/json'
}

result = RestClient.post 'https://api.fax.ir/v2/accounts/self/outbox',
  params: {
  }, headers: headers

p JSON.parse(result)
```

`POST /accounts/self/outbox`

Send a fax

With this API call you will be able to send a fax (one or more files) to one or more destinations. If you are a corporate member and you don't have a fax number set your **from** parameter to **NO_NUMBER**

Body parameter

```
{
  "to": [
    "string"
  ],
```

```
  "from": "string",
  "files": [
    "string"
  ],
  "options": {
    "retry": {
      "delay": 0,
      "count": 0
    },
    "enhancement": true
  },
  "send_time": "string",
  "comment": {
    "text": "string",
    "tags": [
      "string"
    ]
  }
}
```


PARAMETERS

Parameter	In	Type	Required	Description
body	body	Outbox	false	Request object to make a new outbox object
» from	body	string	false	No description
» options	body	object	false	No description
»» retry	body	object	false	No description
»»» delay	body	integer	false	No description
»»» count	body	integer	false	No description
»» enhancement	body	boolean	false	No description
» send_time	body	string	false	No description
» comment	body	object	false	No description
»» text	body	string	false	No description
»» tags	body	[string]	false	No description
» to	body	[string]	false	No description
» files	body	[string]	false	No description

RESPONSES

Status	Meaning	Description
201	Created	Outbox fax has been created successfully
400	Bad Request	No description
500	Internal Server Error	No description

getOutboxFax

Code samples

```ruby
require 'rest-client'
require 'json'

headers = {
  'Accept' => 'application/json'
}

result = RestClient.get 'https://api.fax.ir/v2/accounts/self/outbox/{outbox_fax_id}',
  params: {
  }, headers: headers

p JSON.parse(result)
```

`GET /accounts/self/outbox/{outbox_fax_id}`

Get an outbox record

Get an outbox fax record information

PARAMETERS

Parameter	In	Type	Required	Description
outbox_fax_id	path	string	true	No description

RESPONSES

Status	Meaning	Description
200	OK	No description
400	Bad Request	No description
500	Internal Server Error	No description

---

deleteOutboxFax

Code samples

```ruby
require 'rest-client'
require 'json'

headers = {
  'Accept' => 'application/json'
}

result = RestClient.delete 'https://api.fax.ir/v2/accounts/self/outbox/{outbox_fax_id}',
  params: {
  }, headers: headers

p JSON.parse(result)
```

`DELETE /accounts/self/outbox/{outbox_fax_id}`

Delete a fax from outbox

Delete a fax that is being sent and is still in your outbox

PARAMETERS

Parameter	In	Type	Required	Description
outbox_fax_id	path	string	true	No description

Example responses

```
{}
```

RESPONSES

Status	Meaning	Description
204	No Content	204 will be returned on successful fax deletion from outbox
400	Bad Request	No description
500	Internal Server Error	No description

STATUS CODE 204

{}

---

updateOutboxFax

Code samples

```
require 'rest-client'
require 'json'

headers = {
  'Content-Type' => 'application/json',
  'Accept' => 'application/json'
}

result = RestClient.put 'https://api.fax.ir/v2/accounts/self/outbox/{outbox_fax_id}',
  params: {
  }, headers: headers

p JSON.parse(result)
```

`PUT /accounts/self/outbox/{outbox_fax_id}`

Modify a fax record in outbox

Modify outbox record's comment

Body parameter

```
{
  "comment": "string"
}
```

PARAMETERS

Parameter	In	Type	Required	Description
outbox_fax_id	path	string	true	No description
body	body	OutboxModification	false	Request object for making changes in an outbox object

Parameter	In	Type	Required	Description
» comment	body	string	false	No description

Example responses

```
{}
```

RESPONSES

Status	Meaning	Description
204	No Content	204 will be returned on successful fax modification in outbox
400	Bad Request	No description
500	Internal Server Error	No description

STATUS CODE 204

{}

Schemas

Outbox


```
{
  "files": [
    "/transient-29362c0c-eeff-45c1-9f4e-4ef5865a41df"
  ],
  "src": "+982189780000",
  "retry": {
    "count": 0,
    "delay": 0
  },
  "should_enhance": false,
  "uid": "53a1afb8585345a39033857e1f36bf8d",
  "designated_src": "",
  "ip": "8.8.8.8",
  "page_count": 0,
  "comment": {
    "text": "",
    "tags": []
  },
  "id": "13a4afb0585345639733857e8f36df8d",
  "file_changes": [],
  "to": [
    "+982189780000"
  ],
  "status": "submitted",
  "status_changes": [
    {
      "status": "submitted",
      "at": "2017-09-24 06:43:04"
    }
  ],
  "contact_name": "",
  "send_time": "2017-09-24 06:43:04 +0000",
  "initiated_from": {
    "type": "",
    "from_id": ""
```

```
  },
  "submit_time": "2017-09-24 06:43:04 +0000",
  "last_updated_status_time": "2017-09-24 06:43:04",
  "options": {},
  "extra_info": {}
}
```


PROPERTIES

Name	Type	Required	Description
src	string	false	No description
retry	object	false	No description
» count	integer	false	No description
» delay	integer	false	No description
should_enhance	boolean	false	No description
uid	string	false	No description
designated_src	string	false	No description
ip	string	false	No description
page_count	integer	false	No description
comment	object	false	No description
» text	string	false	No description
» tags	[string]	false	No description
id	string	false	No description
status	string	false	No description
contact_name	string	false	No description
send_time	string	false	No description
initiated_from	object	false	No description
» type	string	false	No description
» from_id	string	false	No description
submit_time	string	false	No description
last_updated_status_time	string	false	No description
options	object	false	No description
extra_info	object	false	No description
files	[string]	false	No description
file_changes	[Unknown]	false	No description
» at	string	false	No description
» files	[Unknown]	false	No description

Name	Type	Required	Description
»» file_name	string	false	No description
»» mime_type	string	false	No description
»» size	number	false	No description
to	[string]	false	No description
status_changes	[Unknown]	false	No description
» status	string	false	No description
» at	string	false	No description

Fax


```
{
  "comment": "",
  "cost": 0,
  "duration": 0,
  "from": "+982189780000",
  "id": "59be3eb357c78d0501081bd7",
  "is_read": false,
  "last_update": "2017-09-17 09:21:55",
  "owner_id": "7724157c0974440293e45877c57f0703",
  "to": "+982189780000",
  "cost_details": {
    "multiplier": 1,
    "notification_cost": 1
  },
  "description": "File Not Found",
  "file": "/transient-2937237320213-213-21323",
  "file_name": "fax-to-982189780000",
  "header": "",
  "max_retry": {
    "count": 0,
    "delay": 0
  },
  "pages": 0,
  "retry_delay": 0,
  "scheduled_time": "2017-09-17 09:21:54 +0000",
  "is_spam": false,
  "status": "failed_file_not_found",
  "submit_time": "2017-09-17 09:21:54 +0000",
  "direction": "outgoing",
  "start_time": "2017-09-17 09:21:54"
}
```


PROPERTIES

Name	Type	Required	Description
id	string	false	No description
comment	string	false	No description
cost	integer	false	No description
direction	string	false	No description

Name	Type	Required	Description
from	string	false	No description
status	string	false	No description
scheduled_time	string	false	No description
description	string	false	No description
is_spam	boolean	false	No description
submit_time	string	false	No description
cost_details	object	false	No description
» notification_cost	number	false	No description
» multiplier	number	false	No description
header	string	false	No description
file	string	false	No description
file_name	string	false	No description
retry_delay	integer	false	No description
max_retry	integer	false	No description
pages	integer	false	No description
start_time	string	false	No description
to	string	false	No description
duration	integer	false	No description
last_update	string	false	No description
is_read	boolean	false	No description
owner_id	string	false	No description

Number


```
{
  "acquired_date": "2017-07-31 09:20:06",
  "assigned_to": "7724157c0974440293e45877c57f0703",
  "expiration_date": null,
  "id": "e6e68ef87f0b8768ebacdb218994bfe7",
  "is_canceled": false,
  "notifications": [
    {
      "email": true,
      "push_notification": true,
      "type": "voicemail"
    },
    {
      "email": true,
      "push_notification": true,
```

```
      "type": "receive_fax"
    },
    {
      "email": true,
      "push_notification": true,
      "type": "announcement"
    },
    {
      "email": true,
      "push_notification": true,
      "type": "callforward"
    }
  ],
  "number": "+982189780000",
  "owner_id": "7724157c0974440293e45877c57f0703",
  "status": "active"
}
```


PROPERTIES

Name	Type	Required	Description
id	string	false	No description
status	string	false	Status of your fax phone number e.g. active, inactive.
is_canceled	boolean	false	No description
expiration_date	string	false	No description
number	string	false	No description
acquired_date	string	false	No description
assigned_to	object	false	No description
owner_id	string	false	No description
notifications	[Unknown]	false	No description
» type	string	false	No description
» email	boolean	false	No description
» push_notification	boolean	false	No description

Account


```
{
  "account_data": {
    "company_name": "Company name",
    "default_file_type": "pdf",
    "save_history": true
  },
  "account_type": "corporate_admin",
  "creation_date": "2017-05-06 05:22:21",
  "email": "sample@fax.ir",
  "last_password_modification_date": "2017-05-06 05:22:21",
  "lastname": "Smith",
  "member_of": {},
  "notifications": {
    "black_list": {
      "uids": []
    },
```

```
    "settings": {
      "email": {
        "addresses": [
          "sample@fax.ir"
        ],
        "low_credit": true,
        "new_feature": true,
        "receive_fax": true,
        "send_fax": true,
        "voicemail": true
      },
      "language": "fa",
      "push_notifications": {
        "low_credit": true,
        "new_feature": true,
        "receive_fax": true,
        "send_fax": true,
        "voicemail": true
      },
      "sms": {
        "low_credit": true,
        "new_feature": true,
        "numbers": [
          "+989350000000"
        ],
        "receive_fax": true,
        "send_fax": true,
        "voicemail": true
      }
    }
  },
  "phone": "+989350000000",
  "profile_image": "",
  "settings": {
    "caller_id_name": "FAX.IR",
    "send_fax": {
      "options": {},
      "retry": {
        "count": 0,
        "delay": 0
      },
      "should_enhance": true
    }
  },
  "status": "active",
  "uid": "7724157c0974440293e45877c57f0703"
}
```


PROPERTIES

Name	Type	Required	Description
status	string	false	Your account status which could be active, inactive etc
account_type	string	false	Account type which could be corporate_admin, individual, etc
lastname	string	false	Your last name
profile_image	string	false	Profile image path
creation_date	string	false	creation date in UTC in the format of YYYY-MM-DD
phone	string	false	Your account phone number
last_password_modification_date	string	false	The date in which you have changed your password
uid	string	false	user id of current user
account_data	object	false	No description

Name	Type	Required	Description
» default_file_type	string	false	Default file type that fax server uses to send the fax
» save_history	boolean	false	Save fax CDRs in inbox status
» company_name	string	false	Your company name in case you are corporate admin
name	string	false	your first name
settings	object	false	No description
» caller_id_name	string	false	Account caller id name
» send_fax	object	false	No description
»» retry	object	false	No description
»»» count	integer	false	No description
»»» delay	integer	false	No description
» should_enhance	boolean	false	No description
» options	object	false	No description
email	string	false	Account email address
notifications	object	false	No description
member_of	[string]	false	No description

File


```
{
  "path": "/storage/2937237320213-213-21323"
}
```


PROPERTIES

Name	Type	Required	Description
path	string	false	Path of newly uploaded file

MemberDetail


```
{
  "quota": 400,
  "role": "Sales Manager"
}
```


PROPERTIES

Name	Type	Required	Description

Name	Type	Required	Description
quota	integer	false	quota of member (number of pages member can send per month)
role	string	false	Role of member in your company

Error

```
{}
```

PROPERTIES

Name	Type	Required	Description
error	string	false	No description
description	string	false	No description